



## Safety Data Sheet

Copyright, 2014 Meguiar's, Inc.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	31-5448-1	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	06/16/14	<b>Supersedes Date:</b>	08/13/13

### SECTION 1: Identification

#### 1.1. Product identifier

D101, Detailer All Purpose Cleaner (22-135B): D10101, D10105

#### Product Identification Numbers

14-1000-0168-5, 14-1000-0169-3, 14-1000-0170-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	Meguiar's, Inc.
<b>DIVISION:</b>	Meguiar's
<b>ADDRESS:</b>	17991 Mitchell South, Irvine, CA 92614, USA
<b>Telephone:</b>	949-752-8000 (Fax: 949-752-5784)

#### 1.4. Emergency telephone number

CHEMTREC 1-800-424-9300 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Corrosive to metal: Category 1.  
Serious Eye Damage/Irritation: Category 1.  
Skin Corrosion/Irritation: Category 1.  
Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (respiratory irritation): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Corrosion | Exclamation mark | Health Hazard |

### Pictograms



### Hazard Statements

May be corrosive to metals.

Causes serious eye damage.

Causes severe skin burns and eye damage.

May cause respiratory irritation.

Causes damage to organs:

blood or blood-forming organs |

Causes damage to organs through prolonged or repeated exposure:

blood or blood-forming organs |

### Precautionary Statements

#### General:

Keep out of reach of children.

#### Prevention:

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

#### Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Absorb spillage to prevent material damage.

#### Storage:

Store in a corrosive resistant container with a resistant inner liner.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause chemical gastrointestinal burns. May cause chemical respiratory tract burns.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	75 - 95 Trade Secret *
Sodium Metasilicate	6834-92-0	1 - 5 Trade Secret *
Mixed Alkyl Sulfates	68439-57-6	1 - 5 Trade Secret *
2-Butoxyethanol	111-76-2	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get immediate medical attention.

**Skin Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Store in a corrosive resistant container with a resistant inner liner. Store away from acids. Store away from oxidizing agents. Store away from areas where product may come into contact with food or pharmaceuticals.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
2-Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	
2-Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	Skin Notation

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield  
 Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Sweet odor; Green liquid
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	13
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	212 °F
<b>Flash Point</b>	Flash point > 93 °C (200 °F) [ <i>Test Method: Closed Cup</i> ]

Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	No Data Available
Vapor Density	No Data Available
Density	1 g/cm <sup>3</sup>
Specific Gravity	1 [Ref Std: WATER=1]
Solubility in Water	Complete
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	No Data Available
Volatile Organic Compounds	2.5 % weight [Details: VOC of concentrate]

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

Strong acids  
Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Corrosion: Signs/symptoms may include nasal discharge, severe nose and throat pain, chest tightness and pain, coughing up blood, wheezing, and breathlessness, possibly progressing to respiratory failure.

May cause target organ effects after inhalation.

##### Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

##### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

##### Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause target organ effects after ingestion.

#### Target Organ Effects:

##### Single exposure may cause:

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE > 50 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Sodium Metasilicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Metasilicate	Ingestion	Rat	LD50 500 mg/kg
Mixed Alkyl Sulfates	Dermal	Rat	LD50 > 2,000 mg/kg
Mixed Alkyl Sulfates	Ingestion	Rat	LD50 578 mg/kg
2-Butoxyethanol	Dermal	Rabbit	LD50 400 mg/kg
2-Butoxyethanol	Inhalation-Vapor (4 hours)	Rat	LC50 2.2 mg/l
2-Butoxyethanol	Ingestion	Rat	LD50 560 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Sodium Metasilicate	Rabbit	Corrosive
Mixed Alkyl Sulfates	Rabbit	Mild irritant
2-Butoxyethanol	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Sodium Metasilicate	Rabbit	Corrosive
Mixed Alkyl Sulfates	Rabbit	Corrosive
2-Butoxyethanol	Rabbit	Severe irritant

**Skin Sensitization**

Name	Species	Value
Sodium Metasilicate	Mouse	Not sensitizing
Mixed Alkyl Sulfates	Guinea pig	Not sensitizing
2-Butoxyethanol	Guinea pig	Not sensitizing

**Respiratory Sensitization**

Name	Species	Value

**Germ Cell Mutagenicity**

Name	Route	Value
Sodium Metasilicate	In Vitro	Not mutagenic
Sodium Metasilicate	In vivo	Not mutagenic
Mixed Alkyl Sulfates	In Vitro	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Mixed Alkyl Sulfates	Dermal	Rat	Not carcinogenic
Mixed Alkyl Sulfates	Ingestion	Rat	Not carcinogenic
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Sodium Metasilicate	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 200 mg/kg/day	during gestation
Mixed Alkyl Sulfates	Ingestion	Not toxic to female reproduction	Rat	NOAEL 871 mg/kg	2 generation
Mixed Alkyl Sulfates	Ingestion	Not toxic to male reproduction	Rat	NOAEL 891 mg/kg	2 generation
Mixed Alkyl Sulfates	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rabbit	NOAEL 600 mg/kg	during organogenesis
2-Butoxyethanol	Dermal	Not toxic to development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis



## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Metasilicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
2-Butoxyethanol	Dermal	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	blood	May cause damage to organs	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	poisoning and/or abuse

## Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Sodium Metasilicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Metasilicate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Metasilicate	Ingestion	blood	All data are negative	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Metasilicate	Ingestion	heart   liver	All data are negative	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Mixed Alkyl Sulfates	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg/day	6 months
Mixed Alkyl Sulfates	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 500 mg/kg	6 months
2-Butoxyethanol	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	All data are negative	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.12 mg/l	90 days
2-Butoxyethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.4 mg/l	14 weeks

2-Butoxyethanol	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	endocrine system	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available

**Aspiration Hazard**

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

**DOTG- Department of Transportation – Ground (United States):**

1 Gallon: LIMITED QUANTITY  
 5/55 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III

**DOTW-Department of Transportation – Vessel (United States):**

1 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III, LIMITED QUANTITY  
 5/55 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III

**IATA-International Air Transport Association (United Nations) :**

1/5 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III  
55 Gallon: Package Size Exceeds IATA Quantity Limitations

**IMO – International Maritime Organization (United Nations):**

1 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III, LIMITED QUANTITY  
5/55 Gallon: UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CONTAINS SODIUM METASILICATE), 8, III

**ID Number(s):**

14-1000-0168-5, 14-1000-0169-3, 14-1000-0170-1

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact manufacturer for more information

**311/312 Hazard Categories:**

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
2-Butoxyethanol (GLYCOL ETHERS)	111-76-2	1 - 5

**15.2. State Regulations**

Contact manufacturer for more information

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

**15.4. International Regulations**

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SECTION 16: Other information**

**NFPA Hazard Classification**

Health: 3    Flammability: 1    Instability: 0    Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	31-5448-1	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	06/16/14	<b>Supersedes Date:</b>	08/13/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. Meguiar's, Inc. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Meguiar's, Inc. product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a Meguiar's, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Meguiar's, Inc. product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Meguiar's, Inc. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Meguiar's, Inc. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from Meguiar's, Inc.

**Meguiar's, Inc. USA SDSs are available at [www.Meguiars.com](http://www.Meguiars.com)**