

---

## SAFETY DATA SHEET

---

### Section 1: IDENTIFICATION

---

**Product Name:** Finish Pro 5000 Lacquer Thinner  
**Product Code:** B10430  
**MSDS Date:** August 5, 2013  
**Cumberland Products Inc**  
50 Commerce Parkway  
Hodgenville, KY 42748  
Phone: 800.223.1918 / Fax 800.500.9812  
Chemtrec (USA): 800.424.9300 For Emergencies

### Section 2: HAZARDS IDENTIFICATION

---

#### EMERGENCY OVERVIEW

**GHS Classification:**

Flammable liquids, Category 2  
Toxic to reproduction, Category 2  
Skin Irritation, Category 2  
Eye irritation, Category 2A  
Specific target organ toxicity – single exposure, Category 1  
Specific target organ toxicity – single exposure, Category 3  
Aspiration hazard, Category 1

**GHS Labeling**



**Symbol:**

**Signal Word:** Danger

**Hazard Statements:**

Highly flammable liquid and vapor  
Suspected of damaging fertility or the unborn child  
Causes skin irritation and serious eye irritation  
Causes damage to organs  
May cause drowsiness or dizziness  
May be fatal if swallowed and enters airways

**Precautionary Statements:**

**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Keep container tightly closed.  
Ground/Bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash hands thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Do not handle until all safety precautions have been read and understood.  
Obtain special instructions before use

Do not breathe mist/vapors/spray  
Do not eat, drink or smoke when using this product  
Avoid breathing mist/vapors/spray

**Response:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/shower

In case of fire: consider carbon dioxide, dry chemical powder, dry sand, limestone powder, or alcohol resistant foam to extinguish

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

**Storage:**

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects:** See Section 11 for more information.

This product does not contain carcinogens or potential carcinogens as listed by IARC, NTP, or ACGIH.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Environmental Effects:** See Section 12 for more information.

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			TWA	STEL	TWA	STEL
1	Methanol CAS #67-56-1	1-100	Not avail	Not avail	200 ppm	250 ppm
2	Toluene CAS #108-88-3	1-100	200 ppm	Not Avail	20 ppm	Not Avail
3	Acetone CAS #67-64-1	1-100	1,000 ppm	Not Avail	500 ppm	Not Avail
4	Light Hydrotreated Distillate CAS #68410-97-9	1-100	5 mg/m <sup>3</sup>	Not Avail	5 mg/m <sup>3</sup>	Not Avail

**Section 4: FIRST AID MEASURES**

Emergency first aid procedures by route of exposure:

**Inhalation:** If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**Ingestion:** Never give anything by mouth to an unconscious person. If a person vomits when lying on his back, place him in the recovery position. Medical care must emphasize the control of acidosis and the use of intravenous bicarbonate has been lifesaving. Evidence is good that treatment of methanol absorption is enhanced through the administration of ethanol, which should be given to produce a blood level of at least 0.1%. Ethanol diminishes the production of toxic metabolites of methanol. Blood methanol level of 50 mg/100mL is an indication for hemodialysis, which has improved the prognosis of methanol intoxication. Methanol is often confused with beverage alcohol (ethylalcohol). Care must be taken to prevent its ingestion, the most frequent cause of methanol poisoning. Prevent aspiration of vomit. Turn victim's head to the side. Do not induce vomiting. If the material is swallowed, get medical attention or advice.

**Skin:** Wash off for 20 minutes. Remove contaminated clothing, and any extraneous chemical.

**Eyes:** Immediately flush eyes with water for at least 20 minutes while holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

**Note to physician:** In case of ingestion or massive inhalation, observe victim as an inpatient because of slow metabolism causes latent period of 24 hours between exposure and acidosis and blindness.

## Section 5: FIRE FIGHTING MEASURES

**Flash Point (Methanol):** 11°C  
**Lower Explosion Limit: (Methanol)** 36.5 %  
**Upper Explosion Limit: (Methanol)** 6%  
**Auto Ignition Temp (Methanol):** 385°C  
**Flammability Classification:** Class IB Flammable Liquid

### Suitable Extinguishing Media:

Use methods appropriate for the surrounding fire. Consider carbon dioxide, dry chemical powder, dry sand, limestone powder, or alcohol resistant foam.

**Products of Combustion:** Incomplete combustion may form carbon monoxide. Fire or intense heat may cause violent rupture of packages. Flash back possible over considerable distance. May form explosive mixtures in air. Downwind personnel must be evacuated. Burning produces obnoxious and toxic fumes. In the event of fire, cool tanks with water spray.

### Fire Fighting Equipment/Instructions:

Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self-contained breathing apparatus for fire-fighting if necessary

HAZARD	HMIS	NFPA
Toxicity	3	3
Fire	3	3
Reactivity	0	0

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Protection:** For large spills wear gloves, Tyvek suits, safety glasses, and appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

**Special Properties:** Flammable Liquid! This material releases vapors at or below ambient temperatures. When mixed with air in certain proportions and exposed to an ignition source, its vapor can cause a flash fire. Use only with adequate ventilation. Vapors are heavier than air and may travel long distances along the ground to an ignition source and flash back. A vapor and air mixture can create an explosion hazard in confined spaces such as sewers. If container is not properly cooled, it can rupture in the heat of a fire.

**Environmental Precautions:** Prevent discharge to open bodies of water, municipal sewers, and watercourses.

**Method for Containment:** Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth. Control runoff and isolate discharged material for proper disposal. Approach release from upwind.

**Methods for Clean-up:** Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container.

## Section 7: HANDLING AND STORAGE

### Handling:

Keep away from heat, sparks and flame. Use only with adequate ventilation.

To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

### Storage:

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Keep away from oxidizers.

## Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### Personal Protective Equipment (PPE)

**Respiratory Protection:** Wear appropriate respirator when ventilation is inadequate.

**Eye/Face Protection:** Splash proof chemical goggles and face shield.

**Hand Protection:** Neoprene gloves, impervious gloves, the breakthrough time of the selected glove(s) must be greater than the intended use period.

**Body:** Avoid skin contact. If product comes in contact with clothing, immediately remove soaked clothing and shower. Wear long sleeve shirts and trousers without cuffs.

### Other Protective Equipment:

Facilities storing or utilizing this material should be equipped with eyewash and safety shower facilities.

See section 3 for exposure limits.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance, State	Clear liquid
Color	Not Available
Odor	Characteristic
pH	Not Available
Vapor Density (Methanol)	0.792 (air = 1)
Boiling Point (Methanol)	148°F (64.55°C)
Vapor Pressure (Methanol)	97.23 mmHg
Melting Point (Methanol)	-144°F (-97.72°C)
Freezing Point	Not Available
Flash Point (See Section 5)	
Flammability Properties (See section 5)	
Solubility (water)	Soluble
Density (Methanol)	49.412 lb/ft <sup>3</sup> (0.7915g/cm <sup>3</sup> )
Evaporation Rate	Not Available

Octanol/Water partition coefficient (Kow) Not Available  
Auto-ignition temperature: Not Available  
Decomposition temperature: Not Available  
Viscosity Not Available

## Section 10: STABILITY AND REACTIVITY

**Stability:** This material is considered stable at ambient temperatures 70°C (21°C).

**Condition to Avoid:** Flames, sparks, electrostatic discharge, heat and other ignition sources.

**Incompatible Materials:** This product reacts with reactive metals (eg. Sodium, calcium, zinc etc), materials reactive with hydroxyl compounds, and oxidizing agents.

**Hazardous Decomposition:** Upon decomposition, this product evolves carbon monoxide, carbon dioxide, aldehydes, and flammable hydrocarbon fragments (eg acetylene).

**Hazardous Reactions:** This product will not undergo polymerization.

## Section 11: TOXICOLOGICAL INFORMATION

### ACUTE EFFECTS:

#### Component Analysis LD50

Methanol (67-56-1)

LD<sub>50</sub>: Oral, Mouse - 7300 mg/Kg

LD<sub>50</sub>: Oral, Rabbit - 14200 mg/Kg

LD<sub>50</sub>: Oral, Rat - 5628 mg/Kg

LD<sub>50</sub>: Skin, Rabbit - 15800 mg/Kg

LC<sub>50</sub>: Inhalation, Rat - 64000 ppm

Acetone (67-64-1)

Oral LD<sub>50</sub> Rat: 5800 mg/kg

LC<sub>50</sub> Inhalation - rat - 8 h - 50,100 mg/m<sup>3</sup>

LD<sub>50</sub> Dermal - guinea pig - 7,426 mg/kg

Skin - rabbit - Mild skin irritation - 24 h

Eyes - rabbit - Eye irritation - 24 h

Toluene (108-88-3)

48 Hr EC<sub>50</sub> Daphnia magna: 5.46 - 9.83 mg/L [Static];

48 Hr EC<sub>50</sub> Daphnia magna: 11.5 mg/L

Inhalation LC<sub>50</sub> Rat 12.5 mg/L 4 h;

Inhalation LC<sub>50</sub> Rat >26700 ppm 1 h;

Oral LD<sub>50</sub> Rat 636 mg/kg;

Dermal LD<sub>50</sub> Rabbit 8390 mg/kg;

Dermal LD<sub>50</sub> Rat 12124 mg/kg

### CHRONIC EFFECTS:

#### Component

Methanol (67-56-1)

**Carcinogenic Effects:** Not available

**Mutagenic Effects:** Laboratory experiments have resulted in mutagenic effects.

**Teratogenic Effects:** Chronic exposure may cause reproductive disorders and teratogenic effects.

**Developmental Toxicity:** Chronic exposure may cause reproductive disorders.

**Target Organs:** Eyes, CNS, skin, GI tract, and respiratory system. **Inhalation:** An irritant to the mucous membranes. Toxic effects exerted upon nervous system, particularly the optic nerve. Once absorbed into the body, it is very slowly eliminated. Symptoms of over-exposure may include headache, drowsiness, nausea,

vomiting, blurred vision, blindness, coma, and death. A person may get better but then worse up to 30 hours later.

**Ingestion:** Toxic. Symptoms similar to those for inhalation, but severity and speed of appearance may be greater. May be fatal or cause blindness. Usual fatal dose: 100 – 125 ml. May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

**Skin Contact:** Methyl Alcohol is a defatting agent and may cause skin to become dry and cracked. Skin absorption can occur in harmful amounts; symptoms may parallel inhalation exposure.

**Eye Contact:** Irritant, characterized by a burning sensation, redness, tearing, inflammation, possible corneal injury, painful sensitization to light. Continued exposure may cause lesions.

**Chronic Exposure:** Marked impairment of vision has been reported. Repeated or prolonged skin contact may cause dermatitis. Chronic exposure may cause reproductive disorders and teratogenic effects. Laboratory experiments have resulted in mutagenic effects.

Acetone (67-64-1)

**Carcinogenicity:** ACGIH A4 – Not Classifiable as a Human Carcinogen

**Neurotoxicity:** This product contains Acetone, a central nervous system target.

**Mutagenicity:** No information available for product.

**Reproductive:** Prolonged skin contact may defat the skin and produce dermatitis in a study of pregnant rats and mice exposed to acetone vapor during 6-19 of gestation, slight developmental toxicity was observed. Reports of other reproductive effects of acetone include observations of testicular effects and changes of sperm quality in rats.

**Developmental:** No information available for product.

**Target Organs:** Acetone can target the respiratory system, eyes, CNS, kidneys, hematology. Narcosis; CNS depression; eye, nose throat, and skin irritation. Harmful if swallowed or inhaled. Can cause CNS depression, drowsiness, narcosis, or asphyxiation. **Skin Contact:** Repeated exposure may cause skin dryness or cracking in human volunteers, topical application of acetone for 30 to 90 minutes produced considerable skin damage with high degree restoration after 72 hours. **Eye contact:** Can cause severe eye irritation. **Inhalation:** Health effects reported in humans caused by inhalation include increase in visual reaction time and decrease in dual response task at 250 ppm; mucous membrane irritation, heavy eyes, headache, and general weakness accompanied by blood changes at 500 ppm; chronic inflammation of airways, stomach and duodenum at 1000 ppm; and severe toxic effects at 4000 ppm. Acetone is readily absorbed into blood stream. **Ingestion:** Symptoms of ingestion include nausea, vomiting, gastric hemorrhage, sedation, respiratory depression, ataxia, and paresthesia.

Toluene (108-88-3)

**Carcinogenic Effects:** A4 - Not classifiable for human or animal by ACGIH.

**Mutagenic Effects:** Not Available.

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Reproductive effects in experimental animals and in long term chemical abuse situations. **Target Organs:** Long-term overexposure to toluene has been associated with impaired color vision. Also, long-term overexposure to toluene in occupational environments has been associated with hearing damage. Skin, respiratory system, Central nervous system, Heart, blood, kidneys, lungs, liver, mucous membrane, brain, eyes, lens, or cornea. **Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours may cause drowsiness and dizziness. **Ingestion** May be harmful if swallowed. Aspiration hazard if swallowed - can enter lungs and cause damage. **Skin** May be harmful if absorbed through skin. Causes skin irritation. **Eyes** Causes eye irritation.

Light Hydrotreated Distillate (CAS #68410-97-9)

**Carcinogenic Effects:** Not Available

**Mutagenic Effects:** Not Available

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Not Available

**Target Organs: Routes of exposure** Inhalation. Ingestion. **Eyes** Avoid contact with eyes. Causes eye irritation. **Skin** Avoid contact with the skin. Contact with skin may cause irritation. **Inhalation** Prolonged inhalation may be harmful.

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity: Methanol (67-56-1)

EC50 (48 h) : 13,200 mg/l Species : Rainbow trout (*Oncorhynchus mykiss*).

EC50 (48 h) : 16,000 mg/l Species : Bluegill sunfish (*Lepomis macrochirus*).

EC50 (48 h) : > 10,000 mg/l Species : *Daphnia*

### Ecotoxicity: Acetone (67-64-1)

96 hour LC50 *Oncorhynchus mykiss*: 5540 mg/L (static)

96 hour LC50 *Pimephales promelas*: 6210 mg/L [flow through]

96 hour LC50 *Lepomis macrochirus*: 8300 mg/L [static]

15 min EC50 *Photobacterium phosphoreum*: 14,500 mg/L

48 Hr EC50 water flea: 0.0039 mg/L

48 hour EC50 water flea: 12,700 mg/L [static]

48 hour EC50 *Daphnia magna*: 12,600 mg/L

### Ecotoxicity: Toluene (108-88-3)

96 Hr EC50 *Pseudokirchneriella subcapitata*: >433 mg/L;

72 Hr EC50 *Pseudokirchneriella subcapitata*: 12.5 mg/L [static] mg/L [flow-through] (1 day old);

96 Hr LC50 *Pimephales promelas*: 12.6 mg/L [static];

96 Hr LC50 *Oncorhynchus mykiss*: 5.89-7.81 mg/L [flowthrough];

96 Hr LC50 *Oncorhynchus mykiss*: 14.1- 17.16 mg/L [static];

96 Hr LC50 *Oncorhynchus mykiss*: 5.8 mg/L [semi-static];

96 Hr LC50 *Lepomis macrochirus*: 11.0-15.0 mg/L [static];

96 Hr LC50 *Oryzias latipes*: 54 mg/L [static];

96 Hr LC50 *Poecilia reticulata*: 28.2 mg/L [semi-static];

96 Hr LC50 *Poecilia reticulata*: 50.87-70.34 mg/L [static]

48 Hr EC50 *Daphnia magna*: 5.46 - 9.83 mg/L [Static];

48 Hr EC50 *Daphnia magna*: 11.5 mg/L

## Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

## Section 14: TRANSPORT INFORMATION

**Proper Shipping Name:** Paint related material

**Hazard Class:** 3

**Identification No.:** UN1263

**Packing Group:** II

**Label:** Flammable

## Section 15: REGULATORY INFORMATION

**TSCA Inventory** This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

**SARA 302/304** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

**SARA 313:** Methanol (CAS #67-56-1) 1.0% de minimus, Toluene (CAS #108-88-3)

**CERCLA** The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: Methanol [CAS No. 67-56-1] RQ = 5,000 lbs, Acetone [CAS No. 67-64-1] RQ = 5,000 lbs, Toluene [CAS No.: 108-88-3] RQ = 1000 lbs, Acetone 5,000 lbs

**SARA 311/312 Hazard** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard, Fire Hazard

#### **Additional Regulatory**

##### **Remarks**

Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains Toluene which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: **DANGER: Contains Toluene! Harmful or fatal if swallowed! Call Physician Immediately. Vapor Harmful! KEEP OUT OF REACH OF CHILDREN!**

#### **Section 16: OTHER SUPPLEMENTAL INFORMATION**

##### Disclaimer:

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Our Company, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will our company be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY Our Company HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.