

## SAFETY DATA SHEET

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: MAESTRO PAINT SEALANT  
 PRODUCT NO: T35  
 RECOMMENDED USE: Automotive Paint Sealant

COMPANY: TRANS-MATE, INC.  
 13 Sterling Road  
 N. Billerica, MA 01862  
 USA  
 978-667-0100

EMERGENCY TELEPHONE NUMBER: Trans-Mate – 978-667-0100  
 CHEMTREC – 800-424-9300

**SECTION 2: HAZARDS IDENTIFICATION****Danger**

Causes eye and skin irritation. Harmful if swallowed or inhaled. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May cause damage to organs (liver, kidney, central nervous system) through prolonged or repeated exposure. Flammable liquid and vapor.

Wear protective gloves and eye protection. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Do not eat drink or smoke when using this product. Keep away from heat and flames. Use explosion-proof equipment. Wash thoroughly after handling.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

If on skin: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

If swallowed: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor immediately if you feel unwell.

Get medical advice if you feel unwell.

In case of fire: Use dry chemical, water fog or carbon dioxide extinguisher.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/ container in accordance with federal, state and local regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

| INGREDIENT            | CAS #      | WEIGHT % |
|-----------------------|------------|----------|
| Aliphatic hydrocarbon | 64742-88-7 | 7-15**   |
| Petroleum distillates | 64742-47-8 | 2-8**    |
| Alumino-silicate      | 1332-58-7  | 2-8**    |
| Polydimethylsiloxane  | 63148-62-9 | 1-5**    |

\*Identity of this ingredient is a trade secret

\*\*Exact percentage of this ingredient is a trade secret

**SECTION 4: FIRST AID MEASURES**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical attention.

If on skin: Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation occurs, get medical attention.

If swallowed: Immediately call a doctor. Do NOT induce vomiting. Rinse mouth.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor immediately if you feel unwell.

**SECTION 5: FIRE FIGHTING MEASURES**

EXTINGUISHING MEDIA: Use water spray, dry chemical, carbon dioxide or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion may produce noxious and irritating gases which will require fresh air source in fire fighting.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

Use personal protective equipment; see Section 8.

Keep product from entering storm sewers and ditches that may lead to waterways.

Stop spill at source; dike and contain large spills and transfer to recovery container. Use absorbent for small spills and containerize.

See Section 13 for disposal.

**SECTION 7: HANDLING AND STORAGE**

Handle according to good manufacturing and warehousing practices. Avoid contact with eyes, skin and clothing.

Store indoors between 40F/4C and 100F/38C

Use product only for intended use. Follow label directions.

Wash hands after handling.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

| INGREDIENT            | CAS #      | OSHA PEL<br>(ppm or *mg.M <sup>3</sup> )<br>+=skin, c=ceiling | ACGIH TLV<br>(ppm or *mg.M <sup>3</sup> )<br>+=skin, c=ceiling |
|-----------------------|------------|---|--|
| Aluminum Silicate     | 66402-68-4 | 5* resp<br>15* total  | 2* resp  |
| Aliphatic hydrocarbon | 64742-88-7 | 500   | 100  |

**EYES:** Wear eye protection (i.e. chemical safety glasses with side shields or goggles). Contact lenses should not be worn.

**SKIN:** Chemical resistant clothing (i.e. gloves) is recommended.

**RESPIRATORY PROTECTION:** Not expected to be needed. Where over-exposure through inhalation may occur from use, approved respiratory protection equipment is recommended.

**VENTILATION:** Local exhaust or general room ventilation is normally adequate.

**OTHER PROTECTIVE EQUIPMENT:** Emergency eye wash station is recommended.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Blue opaque liquid

**ODOR:** Blueberry fragrance

**ODOR THRESHOLD:** NA

**pH:** 8

**MELTING/FREEZING POINT:** Approx. 32F/0C

**BOILING POINT:** APPROX 212F/100C

**BOILING RANGE:** NA

**FLASH POINT (CC):** 112F/44C

**EVAPORATION RATE:** Approx. that of water

**FLAMMABILITY:** Flammable

**UPPER/LOWER FLAMMABILITY LIMITS:** NA

**UPPER/LOWER EXPLOSIVE LIMITS:** 4.9%/0.5% (Aliphatic hydrocarbon)

**VAPOR PRESSURE:** NA

**VAPOR DENSITY:** NA

**RELATIVE DENSITY:** 8.1 LB/GAL

**SOLUBILITY:** Not water soluble

**PARTITION COEFFICIENT: N-OCTANOL/WATER:** NA

**AUTO-IGNITION TEMPERATURE:** NA

**DECOMPOSITION TEMPERATURE:** NA

**VISCOSITY:** Moderately viscous

**SECTION 10: STABILITY AND REACTIVITY**

**REACTIVITY:** Stable

**CHEMICAL STABILITY:** Stable

**POSSIBILITY OF HAZARDOUS REACTIONS:** Low.

**INCOMPATIBLE MATERIALS:** Avoid oxidizers and reducers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and other gases.

**SECTION 11: TOXICOLOGICAL INFORMATION**

This product contains no ingredients at or about 0.1% that are listed by NTP, IARC, or OSHA as carcinogens.

**SECTION 12: ECOLOGICAL INFORMATION**

Ecological data for this chemical mixture is not available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with federal, state and local environmental regulations.

**SECTION 14: TRANSPORT INFORMATION**

| Regulatory information | UN number | Proper shipping name | Class | Packing group | Label | Additional information     |
|------------------------|-----------|----------------------|-------|---------------|-------|----------------------------|
| DOT                    | NA        | NOT REGULATED        | NA    | NA            | -     | Ground transportation only |

**SECTION 15: REGULATORY INFORMATION**

RTK Ingredients : Water (7732-18-5), Aliphatic hydrocarbon (64742-88-7), Petroleum distillates (64742-47-8), Alumino-silicate (1332-58-7) Polydimethylsiloxane (63148-62-9)

**SECTION 16: OTHER INFORMATION**

NFPA 704  
 HAZARD RATING  
 4=Severe H=1  
 3=Serious F=2  
 2=Moderate R=0  
 1=Slight  
 0=Minimal

Prepared: February 12, 2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which maybe the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer or his agent based on its own studies and on the work of others. Neither the manufacturer nor his agent makes any warranty, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. Neither the manufacturer nor his agent shall be held liable (regardless of fault) to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information. Data is supplied for use only in connection with occupational safety and health.